



- CMOS de alto rendimiento de 2 megapíxeles
- Salida de HD analógica, resolución de hasta 1080P
- True Day / Night, Smart IR
- Distancia de infrarrojos de hasta 20 m
- Ip66 resistente a la intemperie
- menú OSD
- Comunicación: Protocolo: HIKVISION-C (Coaxitron))



Camera	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effeecte Pixels	1930(H)*1088(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shuter Time	1/25(1/30)s to 1/50,000s
Lens	3.6mm
	Angle of View: 91.3°(3.6mm), 59.9°(6mm)
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 180°, Rotaton: 0 - 360°
Synchronizaton	Internal synchronizaton
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Rato	> 62dB
Menu	
Camera ID	On/o ff(0-255)
AGC	Support
D/N Mode	Color/BW/Auto/EXT
White Balance	Auto/User/Push/8000K/6000K/4200K/3000K
Privacy Mask	On/Off, maximum 2 zones
Motion D ttection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/Off
Language	English/Chinese
Functons	Digital noise reduction, Mirror
General	
Operatng Condiitions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC± 15%
Power Consumption	Max. 4W
Protecton Level	IP66
IR Range	Up to 20m
Communicaton	Up the coax, Protocol: HIKVISION-C(TVI output)
Dimensions	Φ70×149.5mm (Φ2.76"×5.89")
Weight	400 g